

Electrofusion Welders

Aquafuse AF160 EF Control Unit

The Aquafuse AF160 is a small size, easy to use hand held welder for all non-pressure drainage pipe applications. It provides reliable welding and is suitable for fittings manufactured by Akatherm, Valsir, Coes, Gerberit, Wavisolo and other manufacturers.

FEATURES

Caldertech

- Fitting size range DN16-160mm
- Hand held
- Constant current secondary output
- Soft touch case bag
- Lightweight
- Simple to use



Aquafuse AF 160 EF Control Unit

Electrofusion Welders

Technical Specification

| Input Voltage | 230v |
|--------------------------|--------------|
| Input Frequency | 50-60Hz |
| Input Current [Max. A] | 5A |
| Power Consumption | 1150VA |
| Environmental Protection | IP57 |
| Coupling Size Range | 16mm - 160mm |



Mechanical Information

| Dimensions [HxWxL] | 250 x 115 x 100mm | |
|--------------------|-------------------|--|
| Weight | 3kg | |
| Case Material | ABS | |

| Code | Description |
|-----------|--|
| 01-01-096 | 230v Calder Aquafuse AF160, with soft touch case bag |

Caldertech International Bretfield Court, Dewsbury, West Yorkshire WF12 9BG, UK **T:** +44 (0)1924 469571 E: info@caldertech.com

Caldertech Australasia

Unit 3/30 Juna Drive, Malaga WA 6090, Australia **T:** +61 (0)8 9209 1132 E: sales@caldertech.com.au

